



C|O|P|P|E|N|S

TTQ-120 RS
120 liter gas water heater



Quality characteristics:

- Vitreous enameled tank and expanded polyurethane insulation.
- Anti-corrosive magnesium anode.
- Piezoelectric ignition and atmospheric safety pilot.
- Hanging or supported installation.
- Superior connection.
- Gas Design pressure: 180 mbar
- Gas Connection 1/2"
- Drain Valve included 3/4"
- Pressure valve 3/4" included
- Max Water Temp 65c
- Unit Weight 45 kg
- Made in Argentina

Diameter

43 cm

Height

144 cm

Liters

120 L

Power

4800 Kcal/h
= 19,000 BTU/hr

Recovery

195 L/H

Water Connection

3/4"

Type of gas

Multigas

Insulation

Expanded polyurethane

ON

Piezoelectric

Facility

1

Burner

Electro-galvanized

Energy Efficiency

A



Certification according to the NAG-314
Standard: M01-0682-05-003/M02-0682-05-003





ENGINEERING TRADING CO. LLC

Tel: (+202) 24177443

Fax: (+202) 35365858

Number: 01012235514

Number: 01009928505



A.A Engineering & Trading Co.
Office building #259, Road 90 North,
5 th settlement
New Cairo, Egypt

www.aaco-egypt.com