



POOL & SPA PRODUCT PORTFOLIO



Raypak[®]
A Rheem[®] Company

RESIDENTIAL POOL & SPA HEATERS

GAS HEATERS



AVIA™

264 MBTUH - 399 MBTUH
84% Efficiency
Featuring ProTek Shield™, Raymote connectivity, Low NOx design.



Digital

199 MBTUH - 399 MBTUH
82% Efficiency
Featuring ProTek Shield™, also available as Low NOx, Millivolt, Cupronickel.



ASME Digital

199 MBTUH - 399 MBTUH
82% Efficiency
Featuring ProTek Shield™, also available as Low NOx.



Above Ground

105 MBTUH and 150 MBTUH
82% Efficiency
Analog (106 Model) or Digital Control (156 Model).

ELECTRIC HEATERS



Crosswind™

28 MBTUH - 61 MBTUH
5.8 ~ 5.7 C.O.P. (80,80,80)¹
27 MBTUH - 58 MBTUH
5.6 ~ 5.3 C.O.P. (80,63,80)¹



Classic Series

103 MBTUH - 140 MBTUH
6.0 ~ 5.6 C.O.P. (80,80,80)¹
97 MBTUH - 130 MBTUH
5.7 ~ 5.3 C.O.P. (80,63,80)¹



Compact Series

48 MBTUH - 80 MBTUH
5.7 ~ 6.0 C.O.P. (80,80,80)¹
46 MBTUH - 77 MBTUH
5.5 ~ 5.8 C.O.P. (80,63,80)¹



E3T™

19 MBTUH - 92 MBTUH
5.5 - 27 kW

RESIDENTIAL POOL & SPA HEATERS / ABOVE GROUND POOL PRODUCTS

PROFESSIONAL SERIES



Professional

266 MBTUH - 399 MBTUH
Featuring ProTek Shield™.



Professional X94

399 MBTUH
94% Efficiency



Professional Heat Pump

140 MBTUH - 170 MBTUH
6.1 ~ 5.8 C.O.P. (80,80,80)¹
133 MBTUH - 155 MBTUH
5.8 ~ 5.3 C.O.P. (80,63,80)¹

PROTÉGÉ SERIES



Protégé™ CFP

50 - 180sf, 36psi
0.75 - 1.5 HP, Single & 2-Speed
0.55 - 1.1 kW



Protégé™ SFP

6-Way Top-Mount Valve
14"-28" Diameter
0.75 - 1.5 HP, Single & 2-Speed
0.55 - 1.1 kW
44 lbs. (20 kg) - 319 lbs. (145 kg)



Protégé™ SF

6-Way Top-Mount Valve
14"-28" Diameter
44 lbs. (20 kg) - 462 lbs. (210 kg)



Protégé™ VSP

1.5 HP Variable-Speed
RS485 Modbus
1.3 kW



Protégé™ AGP

0.75-1.5 HP
Single & 2-Speed
0.55 - 1.1 kW

GAS HEATERS



Professional Indirect

1 MMBTUH - 2 MMBTUH
Up to 96% Efficiency
Cupronickel indirect heat exchanger standard. Titanium indirect heat exchanger and warranty upgrade option.
Cascades up to 8 units.



XTherm®

1 MMBTUH - 4 MMBTUH
97% Efficiency
Hybrid: cupronickel finned water-tube heat exchanger with secondary stainless steel condensing water-tube heat exchanger.
Cascades up to 8 units.



MVB®

500 MBTUH - 2 MMBTUH
83-83.3% Efficiency
Cascades up to 8 units.



Hi Delta®

500 MBTUH - 2.3 MMBTUH
83.1% Efficiency
Cascades up to 8 units.
SureRack® vertical racking option.



Raytherm®

511 MBTUH - 4 MMBTUH
82% Efficiency

¹Tested to AHRI 1160

 Raymote Equipped